

ATF Oils



PETROGULF ATF DEXRON IID

Product Data Sheet

PETROGULF ATF Dexron IID are premium quality automatic transmission fluid based on high viscosity index mineral oils and carefully selected additives. It is blended to meet the stringent requirements of leading automotive transmission manufacturers, used in hydraulic applications calling for oils meeting ISO VG 32-46-68 viscosity requirements and power steering units. Suitable for use in all vehicles where GM Dexron® III, Ford Mercon® or Allison C-4 fluids are required. They have dependable anti-wear and gear protection, long component life and excellent oil fluidity at low temperatures.

FEATURES

- Provides consistent, reliable, smooth and trouble free operation of automotive transmission systems.
- Exceptionally high oxidation resistance to oil degradation and keeps automatic transmission clean.
- A special 'VI' improver minimizes the changes in viscosity with operating temperature.

Performance Standards

- ⚡ Allison C-3
- ⚡ 2F-ML-14
- ⚡ MB 236.1
- ⚡ CAT TO-2

Typical Physical Characteristics

ATF		Dexron IID	
Kinematic Viscosity @ 40°C mm ² /s	ISO 3104	33.0-35.0	
@ 100 °C mm ² /s		7.0-8.0	
Viscosity Index	ISO 2909	>135	
Density @ 15°C kg/m ³	ISO 12185	868	
Flash Point COC °C	ISO 2592	>180	
Pour Point °C	ISO 3016	-40	

*These characteristics are typical of current production. Whilst future production will conform to PetroGulf's specification, variations in these characteristics may occur.

HANDLING, HEALTH AND SAFETY

- In normal conditions of use, this lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing, keep away from combustible materials. Store under cover and away from risk of pollution. Dispose off used oil correctly; don't pour down drains, into water courses or the soil.
- Take used oil to an authorized collection point.



www.petrogulflube.com
email : sales@petrogulflube.com
+971-50-6260837,

