

Industrial Oils



PETROGULF UNIVERSAL TRACTOR FLUID (UTF)

Product Data Sheet

PetroGulf Universal Tractor Fluid is a premium hydraulic / transmission fluid that exceeds the refill and service top-up needs of farm and industrial tractor transmission, differentials, and immersed disc brakes. PetroGulf UTF is compounded with anti-wear, extreme pressure, anti-oxidant, and friction control additives and foam and corrosion inhibitors. PetroGulf UTF couples this unique additive package with highly refined base oils and shear stable viscosity index improver for a balanced package.

FEATURES

- Enhanced shear stability and optimized low temperature performance.
- Improved EP wear protection and excellent thermal stability.
- Trouble free hydraulic systems performance
- Smooth operation of the wet brakes and power take off clutches.

PERFORMANCE STANDARDS

- API CF/SF
- Allison C-4
- Massey Ferguson
- John Deere
- API GL-4
- Caterpillar TO-2
- Ford New Holland

TYPICAL CHARACTERISTICS

Table A

PetroGulf UTF		
SAE Grade	15w/40	10w/30
Specific Gravity @ 15°C	0.890	0.880
Flash Point (COC), °C	>210	>200
Viscosity		
cSt @ 40°C	110	73-75
cSt @ 100 °C	14.5-15.5	11-12
Viscosity Index	140	>145
Pour Point, °C	-30	>-36
Sulphated Ash, wt%	1.4	1.4
Total Base No. mg KOH/gm	11	11

These characteristics are typical of current production. Whilst future production will conform to PetroGulf's specification, variations in these characteristics may occur.

HANDLING, HEALTH AND SAFETY

- Lubricants under normal conditions of use, presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off used oil correctly; don't pour down drains, into water courses or the soil.
- Take used oil to an authorized collection point.
- PetroGulf will not accept any liability if the product is used other than in manner or with the precautions for the purpose specified, and hence advice should be obtained from PetroGulf's local office.



www.petrogulflube.com
email : sales@petrogulflube.com
+971-50-6260837,

