

PETROGULF SPARK X SILVER

PETROGULF Spark X Silver lubricants are high quality diesel engine oils, mono and multi-grades, blended for use in high-speed, naturally aspirated and moderately rated turbocharged units. These lubricants incorporate an advanced detergent additive system to control piston deposits and maintain good standards of engine cleanliness & are designed for units burning low sulphur / medium, distillate fuels & long distance trucking and similar constant speed road operations.

Features

- Excellent Total Base Number (TBN) retention to ensure protection throughout the oil drain period.
- Enhanced protection against corrosion and wear.
- High resistance to oxidation and thermal degradation ensuring long oil life and low tendency for deposit formation.

Performance Levels

- API SL/CF, SJ/CF4
- MB' 229.1
- ACEA A31B398
- VW 501.503

Typical Physical Characteristics

SAE Grade	40	50	15W-40	20W-50
Kinematic Viscosity				
@ 40 °C cSt	140	212	100.1	140
@ 100 °C cSt	14.6	18-19	14.6	18-19
Viscosity Index (IP 226)	>95	>95	>145	>140
Density @ 15 °C kg/l (IP 365)	0.895	0.900	0.890	0.894
Flash Point °C (COC) (IP 36)	216	216	>200	>200
Pour Point °C (IP 15)	-9	-9	-27	-20

* These characteristics are typical of current production. Whilst future production will conform to PetroGulf's specification, variations in these Characteristics may occur. The oil drain interval as specified by the engine manufacturer should be adhered to, particularly where indirect fuel Injection is used.

Health & Safety

PetroGulf Oils are unlikely to present any significant health or safety hazard when properly in the recommended application, and good standards of industrial and personal hygiene are maintained. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

For further guidance on Product Health, & Safety, refer to the appropriate PetroGulf Material Safety Data Sheet.

Advice on applications not covered in this leaflet may be obtained from your PetroGulf representative.

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil, or water.

