

PetroGulf Power X Zoom oils are superior quality monograde & multigrade engine lubricants for older petrol and diesel engines. Especially developed to meet the most severe performance requirement of naturally aspirated or turbocharged diesel engines.

FEATURES / BENEFITS

- Offers basic protection for petrol and diesel engines
- High Alkaline content to protect against corrosion
- The oil is formulated to provide reliable protection under most driving conditions and for use in diesel passenger car engines where API CD/SF specification is recommended.

PERFORMANCE STANDARDS

- API CD/SF
- MIL-L 2104 D/, 46152 B
- CCMC D1, D2, PDI
- Caterpillar TO-2, TO-3

TYPICAL CHARACTERISTICS

PetroGulf Power X Zoom				
SAE Grade	15W/40	30	40	50
Specific gravity @ 15°C	0.886	0.895	0.899	0.903
Flash Point (COC), °C	>210	>210	220	240
Kinematic Viscosity				
cSt @ 40°C	112.5	108	168	210
cSt @ 100°C	14.8	10-11	14.5-45.5	18.5-19.0
Viscosity Index	>130	95	95	95
Sulphated Ash, m%	1.20	1.20	1.20	1.20
Total Base Number, mg KOH/gm	11.0	11.0	11.0	11.0
Pour Point, °C	-24	-15	-12	-9

*These characteristics are typical of current production. Whilst future production will conform to PetroGulf's specification, variations in these characteristics may occur.

HANDLING, HEALTH AND SAFETY

- ✚ Lubricants under normal conditions of use, presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- ✚ Prevent any splashing and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off used oil correctly; don't pour down drains, into water courses or the soil.
- ✚ Take used oil to an authorized collection point.
- ✚ PetroGulf will not accept any liability if the product is used other than in manner or with the precautions for the purpose specified, and hence advice should be obtained from PetroGulf's local office.

