



Product Data Sheet

PETROGULF POWER X SUPER DIESEL ENGINE OIL

PetroGulf Super Diesel Engine Oil is available in SAE viscosity grade 30/40/50 & 20W50. It is economy grade engine oil formulated with high quality paraffinic base oils and selected additive packages. It is designed for gasoline engines in passenger cars and trucks, as well as certain aspirated, turbocharged or supercharged diesel engines when API Service Categories SE, SD, or SC are recommended. This product provides oxidation stability and anti-wear performance and offers protection against low temperature engine deposits, rust and corrosion. In addition, it meets or exceeds the diesel engine service requirements of API CC. Oils designed for this service provides protection from high-temperature deposits, bearing corrosion, and fuels with a wide quality range (including high-sulfur fuels).

FEATURES

- ➤ Good high temperature stability and oxidation resistance
- Good protection against corrosion and rusting.
- PERFORMANCE STANDARS
- ➢ API CC/SC
- ➤ MIL-L 2104 B

TYPICAL CHARACTERISTICS

PetroGulf Power X Super Diesel Engine Oil				
SAE Grade	30	40	50	20W50
Specific Gravity, 15°C	0.880	0.890	0.902	
Flash point (COC), °C	220	240	250	>210
Kinematic Viscosity				
cSt @ 40°C	102.0	150.4	237.5	158
cSt @ 100°C	11.0	14.5	19.9	19.0
Viscosity Index	>95	>95	>95	>130
Total Base Number, mg KOH/gm	4.9	4.9	4.9	4.9
Sulphated Ash, m%	>0.50	>0.50	>0.50	>0.50
Pour Point, °C	-8	-6	-6	-21

These characteristics are typical of current production. Whilst future production will conform to PetroGulf's specification, variations in these characteristics may occur.

HANDLING, HEALTH, AND SAFETY

- Lubricant presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off used oil properly; don't pour down drains, into water courses or the soil.
- PetroGulf will not accept any liability if the product is used other than in manner or with the precautions for the purpose specified, and hence advice should be obtained from PetroGulf's local office.

DISCLAIMER: PetroGulf and its subsidiaries will not accept liability if any product is used other than in the manner or with the precautions or for the purpose specified. Advice should be obtained from local PetroGulf office before use.



www.petrogulflube.com
email: sales@petrogulflube.com
+971-50-6260837,